



Knapstein

AURA-L

Oberfläche

- nickel
- black

Technical details

Country of Manufacture	 Germany
Manufacturer	Knapstein
Designer	Knapstein
Protection class / IP rating	IP20
Contents of the package	LED
Projection in cm	50
material	aluminum, metal
dimming	gesture control
LED	inclusive
Colour Rendering Index	>90
Color temperature in Kelvin	2,700 extra warm white
lamp stand dimensions	28 cm
system performance	1 x 43 Watt + 1 x 10.8 Watt
Total luminous flux in lm	6,300
Dimensions	H 184 cm

Description

The Knapstein AURA-L emits its light upwards as a ceiling floodlight. The lamp has a rotating and swivelling reading arm. The lamp head on the reading arm can be swivelled independently of the reading arm. The Uplight of the ceiling floodlight and the light of the lamp head can be switched and dimmed separately by gesture control.

The sensor area for the ceiling floodlight is located in the centre of the light rod, for the reading arm in the lower area of the plexiglass cover at the bottom of the lamp head. The respective light source is switched on or off with a wiping hand movement in the sensor area. To dim the individual light source continuously, the hand is held at or below the sensor for a longer period of time. Using the memory function, the last set light intensity is saved and automatically selected the next time it is switched on. In the event of a mains failure, the light is automatically switched on if it was previously on. It remains switched off if it was also switched off prior to the power failure. This function is suitable for use with switchable sockets.

The AURA-L from Knapstein is available in black and matt nickel-plated surfaces. The floor lamp is also offered without reading arm.